

Application No.: 09/751,623
Amendment Date: September 16, 2005
Reply to Office Action dated: May 18, 2005

LISTING OF THE CLAIMS:

The pending claims are as follows:

1. (Currently Amended) A method for executing a locked bus transaction in a multi-node system, comprising:
 - initiating a locked-bus transaction at a bus agent;
 - transmitting a locked-bus request to a first node controller; and
 - deferring the locked-bus transaction at the bus agent by said first node controller;
and asserting a signal to said bus agent by said first node controller to prevent said bus agent from initiating a bus transaction.
2. (Original) The method of claim 1 further comprising:
 - transmitting the locked-bus request from the first node controller to a second node controller.
3. (Original) The method of claim 2 further comprising:
 - preventing bus transactions on a bus coupled to said second node controller.
4. (Original) The method of claim 3 further comprising:
 - performing the locked-bus transaction by the bus agent over the multi-node system.
5. (Cancelled).

Application No.: 09/751,623

Amendment Date: September 16, 2005

Reply to Office Action dated: May 18, 2005

6. (Currently Amended) The method of claim ~~[[5]]~~1 further comprising:
transmitting the locked-bus request from the first node controller to a second node controller.

7. (Original) The method of claim 6 further comprising:
preventing bus transactions on a bus coupled to said second node controller.

8. (Original) The method of claim 7 further comprising:
deasserting said signal to said bus agent by said first node controller.

9. (Original) The method of claim 8 further comprising:
performing the locked-bus transaction by the bus agent over the multi-node system.

10. (Currently Amended) A multi-node system comprising:
a bus agent to initiate a locked-bus transaction; and
a first node including a first bus and a first node controller to receive a locked-bus request and defer the locked-bus transaction at the bus agent wherein said first node controller is to assert a signal to said bus agent to prevent said bus agent from initiating a bus transaction.

Application No.: 09/751,623

Amendment Date: September 16, 2005

Reply to Office Action dated: May 18, 2005

11. (Original)The system of claim 10 further comprising:

a second node including a second bus and a second node controller to receive the locked-bus request from the first node controller.

12. (Original)The system of claim 11 wherein said second node controller is to prevent bus transactions on said second bus.

13. (Original)The system of claim 12 wherein the bus agent is to perform the locked-bus transaction over the multi-node system.

14. (Cancelled).

15. (Original)The system of claim 14 further comprising:

a second node including a second bus and a second node controller to receive the locked-bus request from the first node controller.

16. (Original)The system of claim 15 wherein said second node controller is to prevent bus transactions on said second bus.

17. (Original)The system of claim 16 wherein said first node controller is to deassert said signal to the bus agent.

Application No.: 09/751,623
Amendment Date: September 16, 2005
Reply to Office Action dated: May 18, 2005

18. (Original) The system of claim 17 wherein the bus agent is to perform the locked-bus transaction over the multi-node system.

19. (Currently Amended) A method for executing a locked bus transaction in a multi-node system, comprising:

initiating a locked-bus transaction at a bus agent;
transmitting a locked-bus request to a first node controller;
deferring the locked-bus transaction at the bus agent by said first node controller;
transmitting the locked-bus request from the first node controller to a switching agent; and
preventing further transactions from said switching agent; and
asserting a signal to said bus agent by said first node controller to prevent said bus agent from initiating a bus transaction.

20. (Original) The method of claim 19 further comprising:
performing the locked-bus transaction by the bus agent over the multi-node system via the switching agent.

21. (Currently Amended) A method for executing a locked bus transaction in a multi-node system, comprising:

initiating a locked-bus transaction at a bus agent for a first I/O node including a first I/O device;
transmitting a locked-bus request to a first node controller; and

Application No.: 09/751,623

Amendment Date: September 16, 2005

Reply to Office Action dated: May 18, 2005

deferring the locked-bus transaction at the bus agent by said first node controller;
and asserting a signal to said bus agent by said first node controller to prevent said bus agent from initiating a bus transaction.

22. (Original)The method of claim 21, further comprising:

transmitting the locked-bus request from the first node controller to the first I/O node.

23. (Original)The method of claim 22, further comprising:

preventing transactions at the first I/O node for I/O devices coupled in said first I/O node.

24. (Original)The method of claim 23, further comprising:

performing the locked-bus transaction by the bus agent over the multi-node system to the first I/O device.